

LED StreetLight PQ2

- Extra Long life
- Up to 10KV Surge Protection
- Impact Resistant
- Dustproof & Waterproof
- Rustproof
- Toolless Maintenance

Application

- Road
- Yard
- Square

Specification

Item Code	Item Description	Power (W)	CCT (K)	Power Factor	Lumen (lm)	Efficacy (lm/W)	Lifespan (LT80B50)
705000108800	LED Streetlight-PQ2 60W-3000-GY-GP	60	3000	0.95	8100	135	50000
705000108900	LED Streetlight-PQ2 60W-4000-GY-GP	60	4000	0.95	8100	135	50000
705000109000	LED Streetlight-PQ2 60W-5700-GY-GP	60	5700	0.95	8100	135	50000
705000114400	LED Streetlight-PQ2 80W-3000-GY-GP	80	3000	0.95	10400	130	50000
705000114500	LED Streetlight-PQ2 80W-4000-GY-GP	80	4000	0.95	10400	130	50000
705000114600	LED Streetlight-PQ2 80W-5700-GY-GP	80	5700	0.95	10400	130	50000
705000109400	LED Streetlight-PQ2 120W-3000-GY-GP	120	3000	0.95	16200	135	50000
705000109500	LED Streetlight-PQ2 120W-4000-GY-GP	120	4000	0.95	16200	135	50000
705000109600	LED Streetlight-PQ2 120W-5700-GY-GP	120	5700	0.95	16200	135	50000
705000109700	LED Streetlight-PQ2 150W-3000-GY-GP	150	3000	0.95	19500	130	50000
705000109800	LED Streetlight-PQ2 150W-4000-GY-GP	150	4000	0.95	19500	130	50000
705000109900	LED Streetlight-PQ2 150W-5700-GY-GP	150	5700	0.95	19500	130	50000
705000110000	LED Streetlight-PQ2 200W-3000-GY-GP	200	3000	0.95	27000	135	50000
705000110100	LED Streetlight-PQ2 200W-4000-GY-GP	200	4000	0.95	27000	135	50000
705000110200	LED Streetlight-PQ2 200W-5700-GY-GP	200	5700	0.95	27000	135	50000

Technical Specifications

CRI	>= 70
Colour Consistency (SDCM)	5
Dimmable	No
Housing Colour	Grey
IP	IP66
IK	IK08
Driver Integrated (Yes/No)	Yes
Glow wire test	650°C
Weight (kg/pc)	2.7/2.7/5.3/5.3/6.4

Electrical Supply

Frequency (Hz)	50/60
Voltage (V)	100-240
AC/DC	AC

Mechanical Properties

Housing Material	Die-cast Aluminum
Optical Material	PC


Application Conditions

Operating Temperature	-35-50°C
Application Temperature	25°C
Storage Environment	-40-65°C

Packaging Information

Item Code	Item Description	Dimensions(mm) (L*W*H)	Gross Weight (kg)	Packing Unit	Packing Qty (pcs/Unit)
705000108800	LED Streetlight-PQ2 60W-3000-GY-GP	445*205*160	3.2		1
705000108900	LED Streetlight-PQ2 60W-4000-GY-GP	445*205*160	3.2		1
705000109000	LED Streetlight-PQ2 60W-5700-GY-GP	445*205*160	3.2		1
705000114400	LED Streetlight-PQ2 80W-3000-GY-GP	445*205*160	3.2		1
705000114500	LED Streetlight-PQ2 80W-4000-GY-GP	445*205*160	3.2		1
705000114600	LED Streetlight-PQ2 80W-5700-GY-GP	445*205*160	3.2		1
705000109400	LED Streetlight-PQ2 120W-3000-GY-GP	540*365*165	6.7		1
705000109500	LED Streetlight-PQ2 120W-4000-GY-GP	540*365*165	6.7		1
705000109600	LED Streetlight-PQ2 120W-5700-GY-GP	540*365*165	6.7		1
705000109700	LED Streetlight-PQ2 150W-3000-GY-GP	540*365*165	6.7		1
705000109800	LED Streetlight-PQ2 150W-4000-GY-GP	540*365*165	6.7		1
705000109900	LED Streetlight-PQ2 150W-5700-GY-GP	540*365*165	6.7		1
705000110000	LED Streetlight-PQ2 200W-3000-GY-GP	615*395*165	7.8		1
705000110100	LED Streetlight-PQ2 200W-4000-GY-GP	615*395*165	7.8		1
705000110200	LED Streetlight-PQ2 200W-5700-GY-GP	615*395*165	7.8		1

Dimensional Drawing



Model	L (mm)	W (mm)	H (mm)
LED SL-PQ2 60W	395	180	123
LED SL-PQ2 80W	395	180	123
LED SL-PQ2 120W	496	340	128
LED SL-PQ2 150W	496	340	128
LED SL-PQ2 200W	572	340	128

Photometric Data

